

MATERIAL SAFETY DATA SHEET

PLAZA Insulating Varnish - CLEAR

1. Product and Company identification

Trade Name	PLAZA Insulating Varnish - CLEAR
Chemical Name	PLAZA Insulating Varnish - CLEAR
ITC (HS) Code	3208
CAS No.	—
Company name and address	PLAZA Chemical Industries 82, Bye pass road Opp. Heera Talkies New Agra Agra 282005 UP India. (+91) 9634046611, (+91) 9319102461 plazachemicals@gmail.com, www.plazachemicals.com

2. Composition / information on ingredients

Ingredient Name : Polyurethane Resin Solution in xylene containing:
PU Copolymer (25%), Xylene (CAS# 1330-20-7, 75%)

3. Hazards Identification

Flammable, Harmful by inhalation and in contact with skin, eyes and respiratory system.

4. First-Aid Measures

After inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do not induce vomiting.

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media
alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)
Extinguishing media which must not be used for safety reasons:
strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13). Clean using cleansing agents. Do not use solvents.

7. Handling and storage**7.1. Precautions for safe handling****Advices on safe handling**

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to chapter 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (BGR 132)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 40 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

8. Exposure controls/personal protection**Exposure controls**

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls**Respiratory protection**

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: gloves made from nitril-/neoprenrubber. Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374. Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

No specific Occupational exposure limit has been established for Acrylic Resin.

9. Physical and chemical properties

Colour on Gardner Scale	: 1
Clarity	: Clear
Acid Value (mg KOH/g of Solid resin)	: Max.10
Flash point	: Above 34 °C (Abel's Close cup)
Solid content (Wt%)	: 25 ± 2
Viscosity (@25°C in BF Viscometer)	: 50-70 PS
solvent content	: Xylene 75 Wt %

10. Stability and reactivity

10.1. Reactivity**10.2. Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials**10.6. Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides

11. Toxicological information

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, dizziness, in serious cases: unconsciousness.

Solvents may cause some of the aforementioned effects through skin resorption.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin.

Splashing may cause eye irritation and reversible damage.

12. Ecological information

There is no information available on the preparation itself. Do not allow to enter into surface water or drains.

Water Hazard Classification No.: WGK2

13. Disposal considerations

Do not allow to enter into surface water or drains. This material and its container must be disposed of in accordance with local regulations. Controlled incineration is recommended.

14. Transport information

Transport only in accordance with the requirements of carriage of dangerous goods.

14.1. **UN number** : 1866

14.2. **UN proper shipping name**

Land transport (ADR/RID): Paint; Sea transport (IMDG): PAINT; Air transport (ICAO-TI / IATA-DGR): Paint

Transport document name: Resin solution/1263 paint related material

14.3. **Transport hazard class(es)** 3

14.4. **Packing group** III

14.5. **Environmental hazards**

Land transport (ADR/RID); Marine pollutant: p

15. Regulatory information

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juvenils according to the "juvenile work protection guideline" (94/33/EC).

Chemical safety assessments for substances in this preparation were not carried out.

16. Other information

The information supplied on this safety data sheet complies with our current level of knowledge. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.